

UbiqCom

Ubiqcom P-52



Model: P-52

Display	<ul style="list-style-type: none"> • Display Resolution: 128x48
Phone Features	<ul style="list-style-type: none"> • Supports SIP2.0 (RFC3261) and Corelative RFCs • Supports 2 SIP servers • Supports SIP UDP/ TCP/ TLS • SIP authentication (none, basic, MD5) • Peer to Peer / IP Call
Feature Keys	<ul style="list-style-type: none"> • Large dot matrix LCD display • Programmable Soft keys & Function keys
Audio Features	<ul style="list-style-type: none"> • HD voice: HD codec • Codec: G.711A/ u, G.723 high/low, G.729a/b, G.722, G.726 • DTMF: In-band, Out - of - band (RFC 2833) and SIP INFO • Full duplex hands- free speaker phone • Voice Activity Detection (VAD) • Comfort Noise Generation (CNG), Echo cancellation: Support G.168, Hand free Speaker Phone
Network Features	<ul style="list-style-type: none"> • WAN / LAN : 10/100M Ethernet ports • Support PPPoE for xDSL • Support VLAN, 802.1X • Support basic NAT and NAPT • NAT Transverse: Support STUN client • Support DNS Relay, SNTP Client • Firewall, VPN (L2TP/Open VPN) and DMZ, • Network tool in telnet Server: Including ping, trace route, Telnet Client
Management Features	<ul style="list-style-type: none"> • WEB, Telnet and keypad management • Upgrade firmware through POST mode and HTTP, FTP or TFTP • Support DHCP option66 and Custom Option, Auto-Provisioning • Telnet remote management/ upload/ download setting file • Safe mode provide reliability • Support Auto Provisioning to upgrade Firmware or configuration file with HTTPS • Support TR-069 and Syslog
Physical Features	<ul style="list-style-type: none"> • Adapter Input :100-240V • Adapter Output : 5V/1A • WAN/LAN Port -10/100 BASE-T • Power: 2.5W/Active: 2.8W • operation Temperature:0~40°C • Relative Humidity 10~65% • Main Chipset - Broadcom • SDRAM - 16MB, FLASH 4MB • Weight - Phone: 0.84kg • Dimension: 250x205x60 mm
Advanced Features	<ul style="list-style-type: none"> • Call forwarding, Call Hold, Call Waiting • Call transfer (blind/ attended/ alert) • Call Conference, Auto Redial • Call Pickup, Call Completion • Support messaging and MWI • Flexible dial plan • Barring function for outgoing calls • Do not disturb, Auto answer, Caller ID display • CLIR (rejects anonymous calls) • CLIP (to make an anonymous call) • Dial without registration • Call Logs: 300 records • Phonebook 500 records • Support SMS and Speed Dial • Hotline/Warm-line, Black List • Intercom/Intercom barge • Support action URL/URI • Voice codec setting for each SIP line • Hands-free ringing choice • Support XML phonebook/browser • Support Click to Dial

Certification

