



Cloud Infotech

IP Telecom Consulting, Integration & Services

PRODUCT BROCHURE

www.cloudinfotech.co.in



ENTERPRISE-LEVEL INNOVATIVE NETWORK SOLUTIONS



CloudEngine



S6730-H SERIES SWITCHES

- 24/48*10 Gig SFP+, 6 x 40/100 Gig QSFP28 Fixed Ports
- Compatible with PVST, PVST+, and RPVST
- 2.4Tbps Switching Capacity

CloudEngine



S5735-L SERIES SWITCHES

- 24 x GE SFP ports, 8 x 10/100/1000Base-T ports, 4 x 10 GE SFP+ ports
- Forwarding performance: 108 Mpps
- Switching capacity: 144 Gbps/432 Gbps

NetEngine 8000 M1A / F1A



- Switching Capacity : Upto 2.4Tbit/s
- Forwarding performance : Upto 453 Mpps
- Capacity Density (G/U) : Upto 1200

OLT

SMARTAX EA5800 SERIES



- The EA5800 provides GPON, XG-PON, XGS-PON, GE, and 10 GE access
- Supports multiple network construction modes, including POL, FTTH, FTTB, and FTTC
- Dual Power Supply

RicherLink



RL80XX EPON/GPON OLT

- 4/8/16 PON Ports, 2/4*10GE SFP+, 4*RJ45
- Pluggable double power supply, double AC, double DC and AC+D
- 4K VLAN Entries, Port-based/MAC-based/IP subnet-based VLA



ONT

EchoLife EG8145V5 / A5

- 1 POTS + 4 GE + Wi-Fi + USB Ports
- Support Dual frequency Wi-fi



RL801G xPON ONU

- 1 PON Port, 1 GE (RJ45) Port
- Wi-Fi : 2.4~2.4835GHz
- ITU-T G.984.2/ITU-T G.984.3/ITU-TG.988 Class B+



RL821GWV xPON ONU

- 1 PON, 2GE, 1 Voice (POTS) Port
- Wi-Fi : 2.4~2.4835GHz
- Supports SIP & H.248 Protocol



RL821GWVD xPON ONU

- 1 PON, 2GE, 1 Voice (POTS) Port
- Dual Band Wi-Fi (2.4, 5.8 GHz)
- Supports SIP & H.248 Protocol





UB5010 G GPON/xPON

- 1 PON, 1*GE (RJ45)
- 28dB Link loss and 20KM distance
- Compatible with third Party OLT



UB5040 G GPON/xPON

- 1 PON, 4*GE (RJ45)
- 28dB Link loss and 20KM distance
- Compatible with third Party OLT



UB5042 GV GPON/xPON

- 1 PON, 4*GE (RJ45), 2*POTS(Voice), 1*USB
- 28dB Link loss and 20KM distance
- Compatible with third Party OLT



UB5010 GW GPON/xPON

- 1 PON, 1GE (RJ45), Wi-fi :2.4 GHz
- 28dB Link loss and 20KM distance
- Compatible with third Party OLT



UB5020 GW GPON/xPON

- 1 PON, 1*GE+1*FE (RJ45), Wi-fi :2.4 GHz
- 28dB Link loss and 20KM distance
- Compatible with third Party OLT



UB5021 GWV GPON/xPON

- 1 PON, 1*GE+1*FE (RJ45), 1 Voice
- Wi-fi :2.4 GHz
- Compatible with third Party OLT



UB5040 GW-D GPON/xPON

- 1 PON, 4*GE (RJ45) Ports
- Dual Band Wi-fi (2.4/5 GHz)
- Compatible with third Party OLT



UB5042 GWV-D GPON/xPON

- 1 PON, 4*GE (RJ45), 2*POTS (Voice)
- Dual Band Wi-fi (2.4/5 GHz)
- Compatible with third Party OLT

OLT

UB50XX EPON/GPON

- 4/8/16 PON Ports, 2*10GE SFP+ Ports
- Combo Ports of 4*GE Ethernet/4 SFP Interfaces
- A complete PON protection switching function



GRANDSTREAM
CONNECTING THE WORLD



OUTDOOR ACCESS POINT

- 2.33Gbps wireless throughput
- Dual-band 4x4:4 MIMO technology
- Support 200+ concurrent Wi-Fi client devices
- Up to 300-meter coverage range



INDOOR ACCESS POINT

- 2.33 Gbps wireless throughput
- Dual-band 4x4:4 MU-MIMO technology
- Supports 200+ concurrent Wi-Fi client
- Up to 175-meter coverage range

cloud Infotech

COMPLETE SOLUTION

FOR YOUR BUSINESS NEED

let's connect 



Cloud Infotech
IP Telecom Consulting, Integration & Services

Cloud Infotech Pvt. Ltd.

Corporate Office : D-92, Sector-63, Noida, UP-201301

Branch Offices : Delhi, Mumbai, Pune, Chandigarh, Bengaluru, Hyderabad, Ahmedabad, Chennai, Kolkata, Kochi

www.cloudinfotech.co.in

Copyright © Cloud InfoTech Pvt. Ltd. All rights reserved.